

RM-2 RAINMAKER

INTERNET BASED 2 WIRE DECODER SYSTEM
IRRIGATION CONTROLLER



Market Sectors

- Agriculture Irrigation
- Landscape Watering
- Golf Irrigation

Benefits

- Can retrofit to legacy Tonick Decoders.
- Remote Control using PC, Smartphones and Tablets over GPRS, 4G, WiFi.
- No app needed, any browser. Web pages in the controller.
- 127 to 508 decoder stations.
- TW/NG-1 decoders programmed and tested using a free App (tamper protected)
- Can sense correct water flow in a valve without needing a flow meter.
- Low cost sensor decoders

Overview

The RM-2 Rainmaker irrigation controller provides a solution for medium to large scale irrigation applications. Providing remote connectivity, the RM-2 is versatile, and is very competitively priced, with many extra features the 'well-known names' do not have. (some patented)

The RM-2 comes with both an Ethernet and an integrated 4G modem providing remote access via a smart phone, tablet, PC or centralised monitoring system. The unit is configured using its own web interface, enabling the user to setup watering stations and program times.

RM-2 RAINMAKER

INTERNET BASED 2 WIRE DECODER SYSTEM IRRIGATION CONTROLLER

Features

- Retrofit to legacy Tonick TW/2W decoders
- Many extra features with next generation TW/NG decoders
 - Decoders programmed and tested using a free NFC app on an Android phone (tamper protection)
 - Valve can be tested using the App
 - Confirmation of water flow through the valve
 - Geo location and installation notes held in the decoder, retrieved by RM-2
- Low cost Flow, Pressure and Moisture Monitoring

Web Page Configuration

The RM-2 has an integrated web server allowing users to operate and configure the RM-2 using a standard web browser. This means it does not need to rely on a 3rd party server, App or proprietary network software.

The web interface will display historic alarms and the current the status of each watering station. The web interface allows the user to test individual or groups of stations by using the manual override feature.



Tonick Decoders

- Next Generation TW/NG-1 family.
- TW/2W Legacy decoders With 1, 2, 3 and 4 outputs.
- Wide variety of TW/NG sensor decoders.
- 5-year warranty, including lightning damage.

Communication Interfaces

- Ethernet, 4G & GPRS, Wifi.

Protocols Supported

- Modbus TCP & RTU, DNP 3.0, Open VPN, SMS.



TWL-Irrigation & Underhill
Wilsonwells Croft
Crimond
Fraserburgh
Aberdeenshire AB43 8YH

01346 531193
sales@twl-irrigation.com
www.twl-irrigation.com